



Cat[®] 323 GC

Hydraulic Excavator

The Cat[®] 323 GC Excavator promotes productivity with easy-to-use controls, a comfortable cab, up to 10 percent increased fuel economy and longer service intervals that reduce operating costs up to 10 percent – all to give you a durable, low-cost per-hour excavator for your applications.

MOVE MORE WITH LESS FUEL

- The C7.1 engine can run on biodiesel up to B20 and the 323 GC meets China Nonroad Stage IV emission standards.
- Use up to 10 percent less fuel than the 323 GC China Nonroad Stage III to keep you moving and productive on the job site.
- The advanced hydraulic system provides the optimum balance of power and efficiency while giving you the control you need for precise digging requirements.
- Valve priority puts hydraulic pressure and flow where you command it to go for fast light- to medium-load cycle times.
- Match the excavator to the job with two power modes; let Smartmode automatically match engine and hydraulic power to digging conditions.
- Auxiliary hydraulic options give you the versatility to use a wide range of Cat attachments.
- Lose less energy and reduce fuel consumption with the positive flow control pump. The pump flow adjusts automatically based on valve priority.
- Advansys™ bucket tips increase penetration and improve cycle times. Tip changes can be done quickly with a simple lug wrench instead of a hammer or special tool, improving safety and uptime. Only available on HD buckets.
- Standard Product Link™ collects data automatically and accurately from your assets – any type and any brand. Information such as location, hours, fuel usage, productivity, idle time, maintenance alerts, diagnostic codes, and machine health can be viewed online through web and mobile applications.

RELIABILITY YOU CAN COUNT ON

- Work up to 3000 m (9,840 ft) above sea level without de-rating.
- Don't let the temperature stop you from working. The excavator has a standard high-ambient temperature capability of 52° C (125°F) and cold start capability of -18° C (0° F).
- Auto warm up speeds up hydraulic oil warming in cold temperatures and helps prolong the life of components.
- Two levels of fuel filtration protect the engine from dirty diesel fuel.
- Grease sealed between track pins and bushings reduces travel noise and prevents debris from entering to increase undercarriage life.
- The track guiding guard helps keep the excavator track aligned when traveling and working on slopes.
- The sloped track frame prevents mud and debris accumulation, helping reduce the risk of track damage.

DESIGNED FOR OPERATORS

- The cab has a wide seat that adjusts for operators of all sizes.
- Control the excavator comfortably with easy-to-reach controls all located in front of you.
- Standard automatic climate control keeps you at the right temperature all shift long.
- Feel more comfortable in the cab while you work with reduced cab vibrations from advanced viscous mounts.
- Stow your gear with plenty of in-cab storage beneath and behind the seat, and in the consoles. A cup holder, document holder, bottle holder, and coat hook are also provided.
- Use the USB ports and Bluetooth® technology to connect to personal devices.



Cat® 323 GC Hydraulic Excavator

SIMPLE TO OPERATE

- Start the engine with the push button, a Bluetooth key fob or the unique Operator ID function.
- Program your power mode and joystick preferences using Operator ID; the excavator will remember what you set each time you go to work.
- Navigate quickly on the standard high-resolution 203 mm (8 in) touchscreen monitor or with the aid of the jog dial control.
- Protect your hammer tool from overheating and rapid wear. Auto hammer stop warns you after 15 seconds of continuous firing and then automatically shuts it off after 30 seconds – all to extend the tool's service life.
- Not sure how a function works or how to maintain the excavator? Always have the operator's manual at your fingertips in the touchscreen monitor.
- Find the tool you need – even if it's hidden beneath overgrowth or debris. Search with your cell phone for any work tool equipped with Cat asset tracking devices up to a range of 60 m (200 ft).

LOWER MAINTENANCE COSTS

- Expect up to 10 percent less maintenance cost than the 323 GC China Nonroad Stage III.
- Do all daily maintenance at ground level.
- Check engine oil level quickly and safely with the new ground-level engine oil dipstick; fill and check engine oil on top of the machine with a conveniently located second dipstick.
- Track your excavator's filter life and maintenance intervals via the in-cab monitor.
- Using Cat genuine oil and filters and doing your typical Scheduled Oil Sampling (S-O-SSM) monitoring will double the current service interval to 1,000 hours, giving you greater uptime to do more work.
- Expect the new air intake filter with integrated pre-cleaner to last up to 1,000 hours in certain applications – a 100 percent increase over the previous filter.
- The new hydraulic oil filter provides improved filtration performance, anti-drain valves to keep oil clean when the filter is replaced, and longer life with a 3,000 hour replacement interval – 50 percent longer than previous filter designs.
- High-efficiency cooling fans run only when needed; you can program intervals so they automatically reverse to keep cores clean without interrupting your work.
- S-O-S ports are on ground level, simplifying maintenance and allowing for quick, easy extraction of fluid samples for analysis.

SAFELY HOME EVERY DAY

- Access 100 percent of daily maintenance points from ground level – no need for you to climb on top of the excavator.
- Keep your excavator secure with Operator ID. Use your PIN code on the monitor to enable the pushbutton starting feature.
- The standard Rollover Protective Structure (ROPS) cab meets ISO 12117-2:2008 requirements.
- Enjoy great visibility into the trench, in each swing direction, and behind you with the help of smaller cab pillars, larger windows, and a flat engine hood design. A rearview camera is standard, and a right-side-view mirror is available.
- New right service platform design provides easy, safe, and quick access to upper service platform; the service platform steps use anti-skid punch plate to prevent slipping.
- The standard hydraulic lockout lever isolates all hydraulic and travel functions in the lowered position.
- Ground-level shut-off switch stops all fuel to the engine when activated and shuts down the machine.

Standard and optional equipment may vary. Consult your Cat dealer for details.

	Standard	Optional
UNDERCARRIAGE AND STRUCTURES		
4700 kg (10,360 lb) counterweight	✓	
600 mm (24") triple grouser shoes	✓	
Tie-down points on base frame (ISO 15818 compliant)	✓	
CAT TECHNOLOGY		
Cat Product Link™	✓	
Auto hammer stop	✓	
CAB		
ROPS, standard sound suppression	✓	
Mechanically adjustable seat	✓	
High-resolution 8" (203 mm) LCD touchscreen monitor	✓	
ENGINE		
Cat C4.4 twin turbo diesel engine	✓	
Two selectable modes	✓	
Auto engine speed control	✓	
Auto engine idle shutdown	✓	
52° C (125° F) high-ambient cooling capacity	✓	
-18° C (0° F) cold start capability	✓	
Double element air filter with integrated pre-cleaner	✓	
Electric fuel priming pump	✓	
Biodiesel capability up to B20	✓	
-32° C (-25° F) cold start capability		✓
BOOM AND STICK		
5.7 m (18'8") Reach boom	✓	
2.9 m (9'6") Optimized Reach stick	✓	

	Standard	Optional
ELECTRICAL SYSTEM		
Two 1,000 CCA maintenance-free batteries	✓	
Programmable time-delay LED working lights	✓	
LED chassis light, left-hand/right-hand boom lights, cab lights	✓	
SERVICE AND MAINTENANCE		
Side entry to service platform	✓	
Grouped location of engine oil and fuel filters	✓	
S-O-S ports	✓	
Ground-level and platform-level engine oil dipsticks	✓	
HYDRAULIC SYSTEM		
Boom and stick regeneration circuits	✓	
Auto warm up	✓	
Auto two-speed travel	✓	
Boom and stick drift reduction valve	✓	
Element type main hydraulic filter	✓	
Combined flow/high pressure auxiliary circuit		✓
Boom and stick hydraulic hammer lines		✓
SAFETY AND SECURITY		
Right-hand handrail and hand hold	✓	
Ground-level engine shutoff switch	✓	
Signaling/warning horn	✓	
Rearview camera and right-hand side mirror		✓
Right hand-sideview camera		✓

Cat® 323 GC Hydraulic Excavator

Technical Specifications

Engine

Net Power – ISO 9249	128.5 kW	172 hp
Engine Model	Cat® C4.4	
Engine Power – ISO 14396	129.4 kW	174 hp
Bore	105 mm	4 in
Stroke	127 mm	5 in
Displacement	4.4 L	269 in ³

Hydraulic System

Main System – Maximum Flow	429 L/min	113 gal/min
Maximum Pressure – Travel	34 300 kPa	4,974 psi
Maximum Pressure – Swing	26 800 kPa	3,886 psi

Swing Mechanism

Swing Speed	11.25 rpm	11.25 rpm
Maximum Swing Torque	82 kN·m	60,300 ft·lbf

Weights

Operating Weight	22 500 kg	49,600 lb
------------------	-----------	-----------

Dimensions

Boom	Reach 5.7 m (18'8")	
Stick	Reach 2.9 m (9'6")	
Bucket	GD 1.3 m ³ (1.7 yd ³)	
Shipping Height – Top of Cab	2960 mm	9.7 ft
Handrail Height	2954 mm	9.7 ft
Shipping Length	9531 mm	31.3 ft
Tail Swing Radius	2833 mm	9.3 ft
Counterweight Clearance	1048 mm	3.4 ft
Ground Clearance	468 mm	1.5 ft
Track Length	4450 mm	15 ft
Length to Center of Rollers	3650 mm	12 ft
Track Gauge	2380 mm	7.8 ft
Transport Width	3650 mm	12 ft

Working Ranges and Forces

Boom	Reach 5.7 m (18'8")	
Stick	Reach 2.9 m (9'6")	
Bucket	GD 1.3 m ³ (1.7 yd ³)	
Maximum Digging Depth	6730 mm	22.1 ft
Maximum Reach at Ground Level	9870 mm	32.4 ft
Maximum Cutting Height	9450 mm	31 ft
Maximum Loading Height	6490 mm	21.3 ft
Minimum Loading Height	2170 mm	7.1 ft
Maximum Depth Cut for 2440 mm (8 ft) Level Bottom	6560 mm	21.5 ft
Maximum Vertical Wall Digging Depth	5610 mm	18.5 ft
Bucket Digging Force – ISO	140 kN	31,518 lbf
Stick Digging Force – ISO	107 kN	23,965 lbf

Service Refill Capacities

Fuel Tank Capacity	345 L	91.1 gal
Cooling System	25 L	6.6 gal
Engine Oil – With Filter	15 L	4 gal
Swing Drive	12 L	3.2 gal
Final Drive – Each	4 L	1.1 gal
Hydraulic System – Including Tank	234 L	61.8 gal
Hydraulic Tank	115 L	30.4 gal
Swing Drive – Each	5 L	1.3 gal
Engine Oil	15 L	4 gal

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

© 2023 Caterpillar
All rights reserved

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow," the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

AEXQ3538 (01-2023)
Build Number: 07F
(China)

